

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.063	T - 1	1.000	0.008	PIANO	0.060	34.000	1.300	0.500
0.094	T - 2	1.000	0.010	PIANO	0.060	0.290	1.930	0.61
	T - 3	1.000	0.012	PIANO	0.120	0.750	1.230	1.05
	T - 4	1.000	0.015	PIANO	0.320	2.580	0.670	2.05
0.125	T - 5	1.000	0.013	INOXIDABLE	0.080	0.370	1.940	0.81
	T - 6	1.000	0.018	PIANO	0.360	2.860	0.770	2.55
	T - 7	1.000	0.020	INOXIDABLE	0.540	4.110	0.590	3.01
	T - 8	1.000	0.020	PIANO	0.570	5.230	0.560	3.51
	T - 9	1.000	0.021	PIANO	0.710	6.210	0.420	3.29
	T - 10	1.500	0.014	PIANO	0.120	0.430	2.540	1.2
	T - 11	1.500	0.015	PIANO	0.160	0.650	2.020	1.47
	T - 12	1.500	0.018	PIANO	0.360	1.680	1.310	2.55
	T - 13	1.500	0.025	PIANO	1.530	11.120	0.490	7.01
	T - 14	2.000	0.013	INOXIDABLE	0.080	0.190	3.830	0.81
	T - 15	2.000	0.020	INOXIDABLE	0.540	1.900	1.270	3.01
	T - 16	2.000	0.022	PIANO	0.870	3.760	1.020	4.69
	T - 17	2.500	0.014	PIANO	0.120	0.240	4.430	1.2
	T - 18	2.500	0.018	PIANO	0.360	0.950	2.300	2.55
	T - 19	4.000	0.016	PIANO	0.220	0.300	5.170	1.79
	T - 20	6.000	0.015	PIANO	0.160	0.140	9.150	1.47
	T - 21	12.000	0.020	PIANO	0.570	0.240	8.710	3.51
0.156	T - 22	1.500	0.020	PIANO	0.340	1.450	1.630	2.71
	T - 23	1.875	0.020	PIANO	0.340	1.120	2.120	2.71
	T - 24	2.500	0.020	PIANO	0.340	0.810	2.930	2.71
0.188	T - 25	0.500	0.015	INOXIDABLE	0.060	0.740	0.970	0.8
	T - 26	0.500	0.020	PIANO	0.220	5.390	0.370	2.19
	T - 27	0.500	0.030	PIANO	1.270	53.670	0.110	7.42
	T - 28	1.000	0.022	PIANO	0.330	2.270	1.140	2.91
	T - 29	1.000	0.026	INOXIDABLE	0.650	4.710	0.720	4.12
	T - 30	1.500	0.015	PIANO	0.070	0.170	5.080	0.94
	T - 31	1.500	0.016	PIANO	0.090	0.230	4.470	1.13
	T - 32	1.500	0.018	PIANO	0.140	0.450	3.250	1.61
	T - 33	1.500	0.020	PIANO	0.220	0.830	2.380	2.19
	T - 34	1.500	0.022	PIANO	0.330	1.390	1.860	2.91
	T - 35	1.500	0.023	PIANO	0.400	1.890	1.560	3.35
	T - 36	1.500	0.025	PIANO	0.580	2.650	1.410	4.3
	T - 37	1.875	0.025	PIANO	0.580	2.030	1.840	4.3

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.188	T - 38	2.000	0.020	INOXIDABLE	0.210	0.470	3.450	1.88
	T - 39	2.000	0.020	PIANO	0.220	0.600	3.270	2.19
	T - 40	2.500	0.018	PIANO	0.140	0.250	5.910	1.61
	T - 41	2.500	0.020	PIANO	0.220	0.440	4.530	2.19
	T - 42	3.313	0.020	PIANO	0.220	0.350	5.690	2.19
	T - 43	5.000	0.023	PIANO	0.400	0.440	6.670	3.35
	T - 44	6.000	0.023	PIANO	0.400	0.360	8.180	3.35
0.219	T - 45	1.500	0.023	PIANO	0.290	1.130	2.250	2.83
	T - 46	2.500	0.023	PIANO	0.290	0.570	4.480	2.83
0.250	T - 47	0.656	0.015	PIANO	0.040	0.390	1.340	0.55
	T - 48	0.688	0.031	PIANO	0.760	15.800	0.330	2.91
	T - 49	0.688	0.034	PIANO	1.120	23.830	0.220	6.27
	T - 50	0.688	0.025	INOXIDABLE	0.290	2.960	0.800	2.65
	T - 51	0.688	0.029	PIANO	0.570	6.500	0.660	4.83
	T - 52	0.688	0.032	INOXIDABLE	0.820	11.730	0.400	5.48
	T - 53	0.719	0.021	PIANO	0.150	1.610	1.070	1.86
	T - 54	0.734	0.020	PIANO	0.120	1.510	0.980	1.6
	T - 55	0.750	0.031	PIANO	0.760	10.990	0.470	5.91
	T - 56	0.735	0.030	PIANO	0.660	8.930	0.520	5.33
	T - 57	0.797	0.030	PIANO	0.660	6.830	0.680	5.33
	T - 58	0.813	0.020	PIANO	0.120	1.080	1.370	1.6
	T - 59	0.844	0.029	PIANO	0.570	7.390	0.580	4.83
	T - 60	0.875	0.020	PIANO	0.120	0.820	1.800	1.6
	T - 61	0.875	0.022	PIANO	0.180	1.580	1.230	2.12
	T - 62	0.875	0.026	PIANO	0.360	3.080	1.010	3.48
	T - 63	0.875	0.032	PIANO	0.870	12.120	0.460	6.47
	T - 64	0.906	0.032	INOXIDABLE	0.820	8.430	0.540	5.48
	T - 65	0.938	0.020	PIANO	0.120	0.730	2.040	1.6
	T - 66	0.938	0.025	PIANO	0.300	2.290	1.230	3.12
	T - 67	0.969	0.027	PIANO	0.420	2.810	1.240	3.91
	T - 68	0.969	0.031	PIANO	0.760	7.660	0.670	5.91
	T - 69	0.969	0.048	INOXIDABLE	4.850	55.670	0.250	18.87
	T - 70	0.984	0.030	PIANO	0.660	5.610	0.830	5.33
	T - 71	1.000	0.021	PIANO	0.150	0.830	2.060	1.86
	T - 72	1.000	0.024	PIANO	0.260	1.410	1.760	2.74
T - 73	1.000	0.047	INOXIDABLE	4.420	59.160	0.260	17.63	
T - 74	1.000	0.049	PIANO	5.320	0.070	0.240	20.1	

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.250	T - 75	1.500	0.015	PIANO	0.040	0.070	9.090	0.69
	T - 76	1.500	0.016	PIANO	0.050	0.120	6.790	0.83
	T - 77	1.500	0.017	INOXIDABLE	0.060	0.130	6.200	0.85
	T - 78	1.500	0.020	PIANO	0.120	0.320	4.590	1.6
0.344	T - 118	1.500	0.025	PIANO	0.150	0.400	5.110	2.2
	T - 119	1.500	0.028	PIANO	0.240	0.810	3.450	3.05
	T - 120	1.875	0.025	PIANO	0.150	0.310	6.640	2.2
	T - 121	2.500	0.025	PIANO	0.150	0.210	9.580	2.2
	T - 122	2.500	0.028	PIANO	0.240	0.400	7.010	3.05
0.375	T - 123	1.000	0.031	PIANO	0.310	3.110	1.110	3.76
	T - 124	1.500	0.039	PIANO	0.800	3.810	1.350	5.95
	T - 125	1.500	0.041	PIANO	0.990	4.790	1.240	6.92
	T - 126	1.500	0.047	PIANO	1.780	9.250	0.920	10.33
	T - 127	1.500	0.062	PIANO	5.920	43.290	0.410	23.74
	T - 128	2.000	0.031	PIANO	0.310	0.900	3.840	3.76
	T - 129	2.000	0.041	PIANO	0.990	3.110	1.900	6.92
	T - 130	2.000	0.058	PIANO	4.420	18.910	0.790	19.43
	T - 131	2.500	0.034	PIANO	0.450	0.810	4.320	3.97
	T - 132	2.500	0.041	PIANO	0.990	2.280	2.600	6.92
	T - 133	3.000	0.028	PIANO	0.200	0.230	11.000	2.77
	T - 134	3.000	0.031	PIANO	0.310	0.410	8.360	3.76
	T - 135	3.000	0.031	PIANO	0.990	1.820	3.260	6.92
	T - 136	3.000	0.047	PIANO	1.780	3.630	2.350	10.33
	T - 137	3.000	0.065	PIANO	7.290	21.670	0.930	27.39
	T - 138	3.500	0.041	PIANO	0.990	1.510	3.910	6.92
	T - 139	3.500	0.054	PIANO	3.240	6.630	1.880	15.68
	T - 140	3.500	0.062	PIANO	5.920	14.430	1.230	23.74
	T - 141	3.625	0.034	PIANO	0.450	0.760	4.620	3.97
	T - 142	4.000	0.034	PIANO	0.450	0.470	7.540	3.97
	T - 143	4.000	0.041	PIANO	0.990	1.290	4.580	6.92
	T - 144	4.000	0.048	PIANO	1.950	3.120	2.900	10.99
	T - 145	4.000	0.054	INOXIDABLE	3.080	5.000	2.690	16.78
	T - 146	4.000	0.063	PIANO	6.350	13.560	1.370	24.88
	T - 147	4.500	0.028	PIANO	0.200	0.150	17.140	2.77
T - 148	4.500	0.031	PIANO	0.310	0.260	13.340	3.76	
T - 149	4.500	0.041	PIANO	0.990	1.130	5.250	6.92	
T - 150	4.500	0.047	PIANO	1.780	2.370	3.610	1.33	

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.375	T - 151	5.000	0.034	PIANO	0.450	0.370	12.090	4.91
	T - 152	5.000	0.054	INOXIDABLE	3.080	3.870	3.470	16.78
	T - 153	6.000	0.041	PIANO	0.990	0.810	7.290	6.92
	T - 154	7.000	0.041	PIANO	0.990	0.690	8.590	6.92
0.437	T - 155	1.000	0.041	INOXIDABLE	0.670	4.380	1.230	6.16
	T - 156	1.000	0.055	PIANO	2.460	33.710	0.340	13.87
	T - 157	8.000	0.031	PIANO	0.310	0.130	25.620	3.76
	T - 158	1.500	0.028	PIANO	0.140	0.540	4.100	2.35
	T - 159	1.500	0.041	PIANO	0.710	2.840	1.800	5.84
	T - 160	1.500	0.047	PIANO	1.260	6.220	1.540	10.82
	T - 161	1.875	0.047	PIANO	1.260	4.300	2.220	10.82
	T - 162	2.000	0.050	PIANO	1.610	5.540	1.580	10.41
	T - 163	2.000	0.062	PIANO	4.130	17.140	0.920	19.82
	T - 164	2.500	0.028	PIANO	0.140	0.180	12.050	2.35
	T - 165	2.500	0.047	PIANO	1.260	2.960	3.230	10.82
	T - 166	2.500	0.062	PIANO	4.130	13.890	1.130	19.82
	T - 167	2.750	0.034	PIANO	0.320	0.500	6.110	3.36
	T - 168	3.000	0.041	INOXIDABLE	0.670	0.970	5.530	6.16
	T - 169	3.500	0.047	PIANO	1.260	1.970	3.770	8.69
	T - 170	3.500	0.050	PIANO	1.640	2.650	3.310	10.41
	T - 171	3.500	0.054	PIANO	2.280	4.030	2.700	13.14
	T - 172	4.000	0.054	INOXIDABLE	2.160	3.050	3.820	14.06
	T - 173	4.500	0.028	PIANO	0.140	0.090	23.410	2.35
	T - 174	4.500	0.041	PIANO	0.710	0.680	7.530	5.84
	T - 175	6.000	0.062	PIANO	4.130	4.680	3.350	19.82
	T - 176	7.000	0.062	PIANO	4.130	3.870	4.050	19.82
	T - 177	8.000	0.054	PIANO	2.280	1.610	6.740	13.14
	T - 178	8.500	0.047	PIANO	1.260	0.730	10.240	8.69
	T - 179	8.500	0.054	PIANO	2.280	1.490	7.290	13.14
	T - 180	8.500	0.072	PIANO	7.920	7.290	3.200	31.21
	T - 181	9.500	0.062	PIANO	4.130	2.840	5.530	19.82
	T - 182	10.250	0.041	INOXIDABLE	0.710	0.280	18.510	5.84
0.500	T - 183	1.000	0.080	PIANO	9.120	138.210	0.200	36.4
	T - 184	1.500	0.076	PIANO	7.290	62.920	0.380	31.33
	T - 185	1.625	0.080	PIANO	9.120	66.230	0.410	36.4
	T - 186	1.938	0.080	PIANO	9.120	48.170	0.570	36.4
	T - 187	2.000	0.065	PIANO	3.700	17.810	0.890	19.52

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.500	T - 188	2.000	0.072	PIANO	5.760	22.920	0.910	26.62
	T - 189	2.188	0.080	PIANO	9.120	41.830	0.650	36.4
	T - 190	2.250	0.035	PIANO	0.270	0.470	6.200	3.17
	T - 191	2.250	0.046	PIANO	0.850	2.220	4.230	10.24
	T - 192	2.500	0.047	PIANO	0.930	1.930	3.380	7.48
	T - 193	2.500	0.054	INOXIDABLE	1.590	3.370	3.040	12.08
	T - 194	2.500	0.080	PIANO	9.120	33.110	0.820	36.4
	T - 195	3.000	0.072	INOXIDABLE	5.470	12.420	1.830	28.68
	T - 196	3.000	0.091	PIANO	16.100	55.420	0.670	53.32
	T - 197	3.188	0.065	PIANO	3.020	8.290	1.680	16.97
	T - 198	3.500	0.062	PIANO	3.020	5.440	2.560	16.97
	T - 199	3.500	0.072	PIANO	5.760	12.090	1.720	26.62
	T - 200	3.500	0.072	INOXIDABLE	5.170	10.850	2.100	28.68
	T - 201	4.000	0.030	PIANO	0.140	11.000	19.030	2.01
	T - 202	4.000	0.041	PIANO	0.530	0.510	8.800	5.04
	T - 203	4.000	0.054	PIANO	1.680	2.280	4.220	11.29
	T - 204	4.000	0.062	PIANO	3.020	5.110	2.730	16.97
	T - 205	4.000	0.075	PIANO	6.880	13.620	1.700	30.04
	T - 206	4.000	0.080	PIANO	9.120	18.920	1.440	36.4
	T - 207	4.500	0.054	PIANO	1.680	1.910	5.020	11.29
	T - 208	4.500	0.062	PIANO	3.020	4.140	3.360	16.97
	T - 209	5.000	0.072	PIANO	5.760	8.210	2.540	26.62
	T - 210	5.500	0.062	PIANO	3.020	3.280	4.250	16.97
	T - 211	6.000	0.062	PIANO	3.020	3.030	4.600	16.97
	T - 212	6.000	0.080	PIANO	9.120	11.600	2.350	36.4
	T - 213	7.000	0.060	PIANO	2.630	3.080	4.140	15.37
	T - 214	7.000	0.072	PIANO	5.760	5.630	3.700	26.62
T - 215	7.125	0.074	PIANO	6.490	8.140	2.750	28.91	
T - 216	8.500	0.047	PIANO	0.930	0.460	14.140	7.48	
T - 217	8.500	0.054	PIANO	1.680	0.940	10.180	11.29	
0.562	T - 218	2.500	0.072	PIANO	4.400	12.280	1.540	23.25
	T - 219	2.875	0.072	PIANO	4.400	10.770	1.750	23.25
	T - 220	3.000	0.054	PIANO	1.290	2.290	3.770	9.91
	T - 221	3.000	0.054	INOXIDABLE	1.230	1.890	4.870	10.6
	T - 222	3.000	0.091	PIANO	12.140	37.740	0.910	46.31
	T - 223	3.500	0.091	PIANO	12.140	30.430	1.120	46.31
	T - 224	4.000	0.047	PIANO	0.720	0.760	7.750	6.58



DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.562	T - 225	5.000	0.072	PIANO	4.400	5.570	3.390	23.25
	T - 226	5.000	0.072	INOXIDABLE	4.180	4.920	4.160	25.05
	T - 227	5.500	0.091	INOXIDABLE	11.530	15.630	2.450	50.51
	T - 228	6.000	0.072	PIANO	4.400	4.620	4.080	23.25
	T - 229	8.500	0.054	PIANO	1.290	0.640	13.400	9.91
	T - 230	8.500	0.062	PIANO	2.320	1.370	9.150	14.86
	T - 231	8.500	0.080	PIANO	6.920	5.480	4.530	31.72
	T - 232	8.750	0.092	PIANO	12.740	15.500	2.270	47.95
	T - 233	16.500	0.054	PIANO	1.290	0.320	26.840	9.91
0.625	T - 234	1.813	0.072	PIANO	3.450	21.760	0.790	20.6
	T - 235	2.000	0.075	PIANO	4.110	18.230	1.050	23.21
	T - 236	2.500	0.072	PIANO	3.450	10.380	1.650	20.6
	T - 237	2.750	0.062	PIANO	1.830	3.780	3.010	13.2
	T - 238	3.000	0.062	PIANO	1.830	3.550	3.200	13.2
	T - 239	3.000	0.080	PIANO	5.420	15.480	1.460	28.05
	T - 240	3.750	0.072	PIANO	3.450	6.430	2.670	20.6
	T - 241	3.500	0.047	PIANO	0.570	0.620	8.550	5.86
	T - 242	3.500	0.099	PIANO	13.630	32.160	1.210	52.42
	T - 243	3.750	0.075	PIANO	4.110	6.880	2.780	23.21
	T - 244	4.000	0.080	PIANO	5.420	8.870	2.550	28.05
	T - 245	4.000	0.091	INOXIDABLE	8.970	16.080	2.170	44.56
	T - 246	4.500	0.062	PIANO	1.830	1.970	5.780	13.2
	T - 247	5.000	0.047	PIANO	0.570	0.420	12.730	5.86
	T - 248	5.500	0.080	PIANO	5.420	6.380	3.550	28.05
	T - 249	6.000	0.072	INOXIDABLE	3.280	2.800	6.630	22.2
	T - 250	6.500	0.054	PIANO	1.020	0.650	11.990	8.82
	T - 251	6.500	0.080	PIANO	5.420	5.270	4.290	28.05
	T - 252	7.500	0.075	PIANO	4.110	3.120	6.110	23.21
	T - 253	8.500	0.062	PIANO	1.830	0.950	11.940	13.2
T - 254	8.500	0.072	PIANO	3.450	2.140	8.000	20.6	
T - 255	8.500	0.080	PIANO	5.420	3.910	5.790	28.05	
T - 256	8.500	0.091	PIANO	9.440	7.660	4.100	40.84	
T - 257	8.500	0.120	PIANO	31.930	36.450	1.720	94.53	
T - 258	12.000	0.048	PIANO	0.630	0.170	32.890	6.21	
0.667	T - 259	5.000	0.072	PIANO	2.790	2.890	5.450	18.52
0.734	T - 260	2.250	0.105	PIANO	12.060	58.510	0.690	52.3
	T - 261	2.438	0.105	PIANO	12.060	50.150	0.800	52.3

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA	
0.734	T - 262	2.625	0.105	PIANO	12.060	43.880	0.920	52.3	
	T - 263	2.875	0.105	PIANO	12.060	39.010	1.030	52.3	
0.750	T - 264	1.500	0.105	PIANO	11.470	100.180	0.390	51	
	T - 265	2.000	0.054	PIANO	0.690	3.020	2.170	7.23	
	T - 266	2.000	0.091	PIANO	6.200	31.310	0.860	33.1	
	T - 267	2.500	0.072	PIANO	2.300	5.630	2.570	16.8	
	T - 268	1.000	0.091	INOXIDABLE	5.890	13.020	2.270	36.1	
	T - 269	1.125	0.105	PIANO	11.470	32.560	1.210	51	
	T - 270	3.250	0.105	PIANO	11.470	31.010	1.270	51	
	T - 271	3.250	0.062	PIANO	1.230	1.690	5.650	10.8	
	T - 272	3.500	0.135	PIANO	34.490	106.630	0.690	108.42	
	T - 273	3.750	0.105	PIANO	11.470	25.540	1.550	51	
	T - 274	4.000	0.063	PIANO	1.310	1.390	7.180	11.300	
	T - 275	4.000	0.080	PIANO	3.580	5.150	3.730	22.82	
	T - 276	4.500	0.062	PIANO	1.230	1.190	8.070	10.8	
	T - 277	5.000	0.062	PIANO	1.230	1.000	9.540	10.8	
	T - 278	5.000	0.120	PIANO	20.520	35.580	1.550	75.78	
	T - 279	6.000	0.080	PIANO	3.580	3.040	6.340	22.82	
	T - 280	6.000	0.091	PIANO	5.890	5.450	5.440	36.1	
	T - 281	6.500	0.091	PIANO	6.200	5.940	4.530	33.1	
	T - 282	7.000	0.135	PIANO	34.490	50.060	1.480	108.42	
	T - 283	7.500	0.062	PIANO	1.230	0.630	15.270	10.8	
	T - 284	8.500	0.072	PIANO	2.300	1.180	12.290	16.8	
	T - 285	8.500	0.080	PIANO	3.580	2.090	9.190	22.82	
	T - 286	8.500	0.091	PIANO	6.200	4.210	6.380	33.1	
	T - 287	9.500	0.140	PIANO	40.540	44.640	1.780	120.13	
	T - 288	12.625	0.080	PIANO	3.580	1.820	10.560	22.82	
	T - 289	4.000	0.105	PIANO	11.470	5.810	6.800	51	
	0.812	T - 290	4.000	0.091	PIANO	5.180	8.770	2.860	30.25
		T - 291	4.000	0.015	PIANO	9.550	19.780	1.870	46.53
T - 292		8.500	0.120	PIANO	17.000	39.110	1.330	68.99	
T - 293		8.500	0.062	PIANO	1.030	0.420	21.330	9.91	
T - 294		8.500	0.072	PIANO	1.930	0.920	14.690	15.39	
T - 295		8.500	0.080	PIANO	3.000	1.620	11.050	20.89	
T - 296		2.500	0.091	PIANO	5.180	3.230	7.770	30.25	
0.875	T - 297	3.500	0.120	PIANO	14.290	56.540	0.870	63.23	
	T - 298	6.000	0.091	PIANO	4.380	7.720	3.040	27.82	

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
0.875	T - 299	6.000	0.091	PIANO	4.380	3.900	6.020	27.82
	T - 300	6.250	0.125	PIANO	17.040	2.930	2.560	70.57
	T - 301	8.500	0.062	PIANO	0.880	0.330	25.080	9.14
	T - 302	8.500	0.080	PIANO	2.540	1.290	12.960	19.23
	T - 303	8.500	0.105	PIANO	8.050	5.430	6.390	42.72
	T - 304	8.500	0.135	PIANO	23.820	21.820	3.040	90.1
	T - 305	9.000	0.135	PIANO	23.820	19.890	3.330	90.1
	T - 306	9.750	0.105	PIANO	8.050	5.390	6.430	42.72
	T - 307	12.000	0.137	PIANO	25.400	15.850	4.270	93.05
0.938	T - 308	3.000	0.091	PIANO	3.760	7.850	2.810	25.78
	T - 309	8.500	0.062	PIANO	0.760	0.270	28.300	8.49
	T - 310	8.500	0.080	PIANO	2.190	1.080	14.470	17.84
	T - 311	8.500	0.120	PIANO	12.200	8.960	5.160	58.43
1.000	T - 312	2.688	0.094	INOXIDABLE	3.550	10.940	2.190	27.98
	T - 313	2.750	0.150	PIANO	12.520	47.620	1.010	60.49
	T - 314	4.000	0.095	INOXIDABLE	2.710	5.390	4.590	20.91
	T - 315	4.000	0.113	INOXIDABLE	7.730	14.600	2.710	48.15
	T - 316	4.000	0.120	PIANO	10.520	21.080	2.070	54.25
	T - 317	7.000	0.135	PIANO	17.430	18.440	3.230	77.08
	T - 318	8.000	0.105	PIANO	5.960	3.840	8.020	36.85
	T - 319	8.500	0.080	PIANO	1.900	0.860	17.130	16.62
	T - 320	8.500	0.091	PIANO	3.260	1.660	12.480	23.99
	T - 321	8.500	0.120	PIANO	10.520	7.740	5.650	54.25
	T - 322	9.000	0.120	PIANO	10.520	6.860	6.370	54.25
	T - 323	12.000	0.105	PIANO	5.960	2.410	12.760	36.75
	T - 324	12.000	0.120	PIANO	10.520	4.970	8.800	54.25
	T - 325	16.500	0.135	PIANO	17.430	6.710	8.890	77.08
1.062	T - 326	5.000	0.135	PIANO	15.180	22.410	2.530	71.91
	T - 327	5.500	0.120	PIANO	9.180	9.510	4.360	50.68
	T - 328	7.000	0.015	PIANO	5.210	3.660	7.970	34.37
	T - 329	12.000	0.135	PIANO	15.180	7.680	7.380	71.93
	T - 330	16.000	0.105	PIANO	5.210	1.910	15.250	34.37
1.125	T - 331	4.500	0.091	PIANO	2.520	1.330	13.960	21.09
	T - 332	6.000	0.148	PIANO	19.740	17.400	3.960	88.61
	T - 333	6.500	0.148	PIANO	19.740	15.410	4.470	88.61
	T - 334	7.000	0.120	PIANO	8.060	3.340	11.820	47.5
	T - 335	8.000	0.105	PIANO	4.590	1.190	23.310	32.25

DIÁMETRO EXTERIOR	No. DE PARTE	DISTANCIA /GANCHOS	DIÁMETRO ALAMBRE	MATERIAL	TENSIÓN INICIAL	RATE LB / IN	MÁXIMA DEFLECCIÓN	FUERZA
1.250	T - 336	4.500	0.187	PIANO	42.500	100.930	1.120	155.38
	T - 337	6.000	0.192	PIANO	47.680	71.720	1.690	168.98
	T - 338	6.500	0.162	PIANO	22.850	25.620	3.120	102.81
	T - 339	7.000	0.162	PIANO	22.850	22.280	4.720	128
	T - 340	8.000	0.162	PIANO	22.850	19.710	4.060	102.81
	T - 341	8.000	0.177	PIANO	33.480	31.720	3.120	132.57
	T - 342	12.000	0.162	PIANO	22.850	12.450	6.420	102.81
	T - 343	14.000	0.177	PIANO	33.480	16.200	6.120	132.57
1.312	T - 344	12.000	0.135	PIANO	9.420	3.820	12.380	56.65
1.500	T - 345	4.000	0.225	PIANO	61.910	182.310	0.860	218.6
	T - 346	5.000	0.243	PIANO	86.660	194.130	0.960	273.31
	T - 347	7.000	0.243	PIANO	86.660	112.160	1.660	273.31
	T - 348	8.500	0.162	PIANO	15.110	10.670	6.420	83.6
	T - 349	8.500	0.192	PIANO	31.190	25.300	4.170	136.68
	T - 350	14.000	0.148	PIANO	10.310	3.590	14.970	64.03
	T - 351	14.000	0.177	PIANO	22.020	8.990	9.510	107.52
1.500	T - 352	14.000	0.192	PIANO	31.190	13.970	7.550	136.68
	T - 353	18.000	0.165	PIANO	16.330	4.680	14.960	86.32
1.750	T - 354	7.000	0.244	PIANO	61.370	78.510	2.160	230.95
	T - 355	8.000	0.207	PIANO	30.280	26.610	4.260	143.68
1750	T - 356	14.000	0.177	PIANO	15.580	5.430	13.780	90.43
	T - 357	14.000	0.207	PIANO	30.280	12.330	9.190	143.68
2.000	T - 358	8.000	0.207	PIANO	22.430	17.960	5.640	123.65